

Air Intake & Throttle Body Cleaner

Revision date: 19.09.2016

Product code: 1497

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Air Intake & Throttle Body Cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number:

For Germany: +49-361-730730 (24 hours/7 days)

Further Information

Article Number: PWT2801

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

xylene

acetone; propan-2-one; propanone

Signal word: Danger

Pictograms:



Air Intake & Throttle Body Cleaner

Revision date: 19.09.2016

Product code: 1497

Page 2 of 10

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe Gas/vapour/aerosole.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye/face protection.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Alcohols.
ketone.
Corrosion inhibitors.

Air Intake & Throttle Body Cleaner

Revision date: 19.09.2016

Product code: 1497

Page 3 of 10

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
1330-20-7	xylene			25 -< 50 %
	215-535-7		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H312 H332 H315 H319 H335 H373 H304			
67-64-1	acetone; propan-2-one; propanone			20 -< 25 %
	200-662-2		01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
64-17-5	ethanol, ethyl alcohol			10 -< 20 %
	200-578-6		01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
75-28-5	isobutane			10 -< 20 %
	200-857-2		01-2119485395-27	
	Flam. Gas 1, Compressed gas; H220 H280			
74-98-6	propane			2,5 -< 10 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1, Compressed gas; H220 H280			
106-97-8	Butane			1,0 -< 2,5 %
	203-448-7		01-2119474691-32	
	Flam. Gas 1, Compressed gas; H220 H280			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.
Change contaminated clothing.

After inhalation

Provide fresh air. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.
In case of skin irritation, seek medical treatment.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.
Harmful: danger of serious damage to health by prolonged exposure through inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

The following symptoms may occur:

Air Intake & Throttle Body Cleaner

Revision date: 19.09.2016

Product code: 1497

Page 4 of 10

unconsciousness. Intoxication. vomiting. drowsiness. Headache.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.
Carbon dioxide (CO₂).
Water fog.
alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Swims on the water. Vapours are heavier than air and will spread at floor level.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear suitable solvent-proof protective clothing according to EN 465. Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes.
Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Explosive. Vapours may form explosive mixtures with air.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep only in the original container in a cool, well-ventilated place.
If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

The floor should be leak tight, jointless and not absorbent. Keep only in the original container in a cool, well-ventilated place. Do not store at temperatures over: 50 °C
Heating causes rise in pressure with risk of bursting.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

Air Intake & Throttle Body Cleaner

Revision date: 19.09.2016

Product code: 1497

Page 5 of 10

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

8.2. Exposure controls

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs.

Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work.

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes.

Hand protection

Tested protective gloves are to be worn: FKM (Fluoroelastomer (Viton)).NBR (Nitrile rubber).

Respiratory protection

Have to care for a good Ventilation at workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	aromatic

Test method

Changes in the physical state

Initial boiling point and boiling range:	<0 °C
Flash point:	-
Ignition temperature:	> 200 °C
Density (at 20 °C):	0,742 g/cm ³
Water solubility: (at 20 °C)	partially soluble
Solvent content:	97,6 %

9.2. Other information

Air Intake & Throttle Body Cleaner

Revision date: 19.09.2016

Product code: 1497

Page 6 of 10

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Do not store at temperatures over: 50 °C
Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No dangerous reactions are known.
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
1330-20-7	xylene			
	oral	LD50 4300 mg/kg	Rat	
	dermal	LD50 3200 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50 21,7 mg/l	Rat	
	inhalative aerosol	ATE 1,5 mg/l		
67-64-1	acetone; propan-2-one; propanone			
	oral	LD50 5800 mg/kg	Rat	RTECS
	dermal	LD50 20000 mg/kg	Rabbit	IUCLID
	inhalative (4 h) vapour	LC50 76 mg/l	Rat	
64-17-5	ethanol, ethyl alcohol			
	oral	LD50 6200 mg/kg	Rat	IUCLID
	inhalative (4 h) vapour	LC50 95,6 mg/l	Rat	RTECS

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.

SECTION 12: Ecological information

12.1. Toxicity

Air Intake & Throttle Body Cleaner

Revision date: 19.09.2016

Product code: 1497

Page 7 of 10

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
1330-20-7	xylene				
	Acute fish toxicity	LC50	26,7 mg/l	96 h	Pimephales promelas
67-64-1	acetone; propan-2-one; propanone				
	Acute fish toxicity	LC50	5540 mg/l	96 h	Onchorhynchus mykiss
	Acute crustacea toxicity	EC50	6100 mg/l	48 h	Daphnia magna
64-17-5	ethanol, ethyl alcohol				
	Acute crustacea toxicity	EC50	9268 - 14221 mg/l	48 h	Daphnia magna
					IUCLID

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

Swims on the water. Low potential of bio-accumulation.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
64-17-5	ethanol, ethyl alcohol	-0,31
75-28-5	isobutane	2,8
74-98-6	propane	2,36

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Arrange about the exact waste code with the local waste disposal expert.

Do not dispose with household waste.

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Contaminated packaging

Dispose of waste according to applicable legislation. Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

SECTION 14: Transport information

Air Intake & Throttle Body Cleaner

Revision date: 19.09.2016

Product code: 1497

Page 8 of 10

Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
 Propane/butane-mixture
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Hazard No: -
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
 Propane/butane-mixture
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
 Propane/butane-mixture
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Marine pollutant: -
 Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)


14.1. UN number: UN 1950

Air Intake & Throttle Body Cleaner

Revision date: 19.09.2016

Product code: 1497

Page 9 of 10

14.2. UN proper shipping name:	AEROSOLS Propane/butane-mixture
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
	
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; Butane

2004/42/EC (VOC): 724,7 g/l

Additional information

Contains:

15 - 30 % hydrocarbons, aliphatic.

> 30 % hydrocarbons, aromatic.

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.

according to Regulation (EC) No 1907/2006

Air Intake & Throttle Body Cleaner

Revision date: 19.09.2016

Product code: 1497

Page 10 of 10

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)